





QUICK FACTS*



MODEL REP33 EA 48



TUCKUNDER MODELS*

MODEL	CAPACITY	LOAD AREA	BED HEIGHT	
REP25 Models	Single-Cylinder			
REP25 EA37	2500 lbs.	37 x 78	37-49	
REP25 EA41	2500 lbs.	41 x 78	39-49	
REP33 Models	Single-Cylinder			
REP33 EA48	3300 lbs.	48 x 78	38-59	
REP33 EA56	3300 lbs.	56 x 78	42-59	

REP44 Models*	Dual-Cylinder		
REP44 EA56	4400 lbs.	56 x 86	43-59
REP44 EA62	4400 lbs.	62 x 86	46-59

^{*}ANTEO* REP44 IS ONLY AVAILABLE FOR 102" WIDE BODIES.

*FOR A FULL OVERVIEW OF STANDARD FEATURES AND AVAILABLE OPTIONS, AS WELL AS COMPLETE DIMENSIONAL DATA AND INSTALLATION INFORMATION, VISIT USA.ANTEO.COM



PLATFORM RIDE

Anteo® REP33 and REP44 Tuckunder platforms tilt to level before leaving the ground, and the platforms remain level throughout their range of motion. The Anteo® REP25 offers a standard-ride, starting level with the truck then gradually tilting to ground level.



POWER-DOWN STANDARD

Power Down comes standard on all Anteo® Tuckunders and offers consistent movement of the platform when lowering. Platform safety flags and pendant control also come standard on every Tuckunder model.



SLEEK & LIGHTWEIGHT

Lifting more than 5x its own weight, the Tuckunder packs 2,500-4,400 lbs lifting capacity in a sleek, compact package.



OPTIONS AVAILABLE

Optional platform lights, foot controls, bed extensions, and more make the Tuckunder highly customizable.

THE NEW ANTEO® USA

With over fifty years of hydraulic industry experience, the latest in liftgate technology, and a commitment to research and quality improvement, Anteo is a truly global name in liftgates.

Now, due to a new American partnership, Anteo products are available in North America like never before. To learn more, visit:







