





TUCKUNDER MODELS*

All models are available for both 96-inch and 102-inch wide bodies

MODEL	CAPACITY	LOAD AREA	BED HEIGHT
REP25 Models	Single-Cylinder • Standard Ride		
REP25 EA37	2500 lbs.	37 x 78	35-47
REP25 EA41	2500 lbs.	41 x 78	37-47

REP33 Models	Dual-Cylinder • Tilt-Up, Level-Ride		
REP33 EA48	3300 lbs.	48 x 81	40-59
REP33 EA56	3300 lbs.	56 x 81	43-59
REP33 EA62	3300 lbs.	62 x 81	46-59
REP44 Models*	Dual-Cylinder • Tilt-Up, Level-Ride		
REP44 EA62	4400 lbs.	62 x 81	46-59

*FOR A FULL OVERVIEW OF STANDARD FEATURES AND AVAILABLE OPTIONS, AS WELL AS COMPLETE DIMENSIONAL DATA AND INSTALLATION INFORMATION, VISIT USA.ANTEO.COM



PLATFORM RIDE

Anteo® REP33 and REP44 Tuckunder platforms tilt to level before leaving the ground, and the platforms remain level throughout their range of motion. The Anteo® REP25 offers a standard-ride, starting level with the truck then gradually tilting to ground level.



POWER-DOWN & BED-EXTENSIONS STANDARD

Power Down comes standard on all Anteo® Tuckunders and offers consistent movement of the platform when lowering. Bed-Extensions, Platform Flags, and a Fixed Toggle Control also come standard on every Tuckunder model. A Bumper Bar comes standard on all REP 33 and REP44 models.



SLEEK & LIGHTWEIGHT

Lifting more than 5x its own weight, the Tuckunder packs 2,500-4,400 lbs lifting capacity in a sleek, compact package.



OPTIONS AVAILABLE

Optional platform lights, foot controls, galvanizing, and more make the Tuckunder highly customizable.

THE NEW ANTEO® USA

With over fifty years of hydraulic industry experience, the latest in liftgate technology, and a commitment to research and quality improvement, Anteo is a truly global name in liftgates.

Anteo products are available in North America like never before. To learn more, visit:







